# **Material Safety Data Sheet**

# **Crystal Nails GEL-LAC**

Page 1 of 6

### Section 1 – Identification

**Product Name: Crystal Nails GEL-LAC** 

Chemical Name: N/A

Family: UV GELS
Product Use: NAIL GEL
Product#: Various

Manufacturer/Distributor: Litrox Factory Investments LLC (443960-91)

US 8130 SW Portland, Oregon, Beaverton-Hillsdale Highway 97225.

### Section 2 - Hazards Identification

#### **EMERGENCY OVERVIEW**

This information may be based on findings from related or similar materials.

• May be slightly toxic.

• May cause moderate skin injury (reddening & swelling).

• May cause eye irritation.

### Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry

No specific information is available for this product. Although, this product opposes only slight irriation concern

with all routes of entry.

Eye No specific information available. Contains materials that are essentially nonirritating, but contact may cause

slight transient irritation.

Skin No specific information available. Contains materials that may cause moderate skin injury (reddening and

swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not

occur immediately, contact can go unnoticed.

Ingestion No specific information available. Contains materials that may be practically nontoxic.

Inhalation No specific information available. Low volatility makes vapor inhalation unlikely.

Sub-Chronic Effects No specific information available. Limited tests showed no evidence of teratogenicity.

NOTE: Refer to Section 11, Toxicological Information for Details

G 4.	•	<b>~</b>	/T C	4.	1 1 4
Section .	<b>5 -</b> (	Compositi	ion/Init	ormation on l	ngredients

Chemical Identity	CAS#	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
•				OSHA ACGI	Ή	_	
				TWA/STEL TW	A/STEL	IARC/NTP/OSHA	
Polyurethane Acrylate	Exempt N/	Е	Di-Hema	N/E N/E		Not Listed	50-60
Oligomer	-		Trimethylhexyl				
			Dicarbamate*				
2-Hydroxyethyl Methacrylate	868-77-9	212-782-2	HEMA	N/E	N/E	Not Listed	5-10
Hydroxypropyl Methacrylate	27813-02-1	248-666-3	Hydroxypropyl	N/E N/E		Not Listed	5-10
			methacrylate				
Polyethylene Glycol 400	25852-47-5 N	N/E	Polyethylene Glycol	N/E N/E		Not Listed	1-6
Dimethacrylate			400 Dimethacrylate				
Isopropyl Alcohol	67-63-0	200-661-7	Isopropyl Alcohol	400 ppm	400 ppm	3/none/none	0-3
n-Butyl Acetate	123-86-4	204-658-1	Butyl Acetate	150 ppm	150 ppm	Not Listed	0-3
Ethyl Acetate	141-78-6	205-500-4	Ethyl Acetate	400 ppm	400 ppm	no/no/no	0-3
Hydroxycyclohexyl phenyl	947-19-3 21	3-426-9	Hydroxycyclohexyl	N/E N/E	-	Not Listed	0-1
ketone			phenyl ketone				

May Contain the following: Please see Section 16 for additional compounds

N/E - None Established N/DA - No Data Available \* See section 16
N/R - Not Reviewed N/A - Not Applicable

**Polyurethane Acrylate Oligomer:** Hazard Symbol: Xi **2-Hydroxy ethyl methacrylate:** Hazard Symbols – Xi

Risk Phrases: R36/37/38 Risk Phrases – R36/38, R43 Safety Phrases: S14, S3/7, S62 Safety Phrases – S2, S26, S28

2-Hydroxy ethyl methacrylate: Hazard Symbols – X1 Risk Phrases – R36/38, R43 Safety Phrases – S2, S26, S28

Hydroxypropyl Methacrylate: Hazard Symbol: Xi Risk Phrases: R36/37/38, R43 Safety Phrases: S26, S36/37

Polyethylene Glycol 400 Dimethacrylate: Hazard Symbol – Risk Phrases – R36/37/38 Safety Phrases – S26, S36, S37

Isopropyl Alcohol: Hazard Symbol – F, Xi Risk Phrases – R11, R36, R67 Safety Phrases – S2, S7, S16, S24/25, S26

**n-Butyl Acetate:** Hazard Symbol: N/E Risk Phrases: R10, R66, R67 Safety Phrases: S2, S25

Ethyl Acetate: Hazard Symbol: F, Xi Risk Phrases: R11, R36, R66, R67 Safety Phrases: S2, S16, S26, S33

# **Material Safety Data Sheet**

# **Crystal Nails GEL-LAC**

Page 2 of 6

See Section 16 for Risk and Safety Phrase Key

### Section 4 - First Aid Measures

First Aid for Eye Flush with plenty of water for 15 minutes and retract eyelids often. Seek medical attention

immediately.

First Aid for Skin Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

First Aid for Inhalation In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing

has stopped, administer artificial respiration and seek medical attention.

First Aid for Ingestion If appreciable quantities are swallowed, seek medical attention.

#### Section 5 - Fire Fighting Measures

Flash Point	Flammable Limit	Auto-ignition Temperature
(°F/°C) (vol%	)	(vol%)
> 73°F/23°C Setaflash	No Data	No Data

Method:

Extinguishing Media: Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.

Fire Fighting Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion

exists.

Unusual Hazards: High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in

explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control

fires since frothing can occur.

#### Section 6 - Accidental Release Measures

Spill or Release Procedures

Storage

Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detregent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

#### Section 7 - Handling and Storage

Handling Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid

prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of

increased penetration potential.

Most acrylic monomers have low viscosities, thus only needing room temperature conditions to facilitate proper pouring techniques. However, viscous type gels such as these may require heating to facilitate proper pouring techniques. To ensure that this happens, product may be heated to 60°C/140°F for not more than 24 hours. Do NOT use localized heat sources such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot rooms are recommended for heating/melting material. The hot box and/or room should only be set to a maximum temperature of 60°C/140°F. Do not overheat, this may compromise product effectiveness and should be avoided. Refrain from multiple reheatings of product, this will also diminishing the quality of the product. Product is extremely light sensitive. If exposed to natural light or UV light, material will cure very quickly. Store

in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above

the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times.

Explosion Hazard High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in

explosions and the violent rupture of storage vessels or containers.

### Section 8 - Exposure Controls / Personal Protection

Engineering Controls Local exhaust recommended to control exposure which may result from operations generating aerosols and hot

operations generating vapors.

# **Material Safety Data Sheet**

# **Crystal Nails GEL-LAC**

Page 3 of 6

**Personal Protective Equipment** 

General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a

hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole

body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection Wear chemical splash goggles.
Skin Protection Wear impervious gloves (Neoprene).

Respiratory Protection A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be

permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN

149.

### Section 9 - Physical and Chemical Properties

Appearance	Odor & Odor Threshold	$_{\mathrm{P}}\mathrm{H}$	Specific Gravity	Viscosity	% Volatile
Clear to slight violet,	characteristic acrylate odor	NA	(H2O=1): 1.15	N/DA	By Volume : < 0.5
viscous liquid					

Boiling Point/ Freezing Point	Decomposition Temperature Pa	Octanol/Water artit ioning Coefficient Log Po/w	Vapor Pressure: Den	Vapor sity	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A	(mm Hg) @ 20 C : < 0.01	No Data	No Data	No Data	Insoluble

Flash Point	Flammable Limit	Auto-ignition Temperature
(°F/°C) (vol%	)	(vol%)
> 73°F/23°C Setaflash	No Data	No Data

### Section 10 - Stability and Reactivity

#### Stability

Normally Stable

### **Incompatibility (Materials to Avoid):**

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.

#### **Hazardous Decomposition Products: Haz**

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.

#### ardous Polymerization:

May occur -- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

#### **Conditions to Avoid:**

Storage >100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

### Section 11 - Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye	
No information available	No information available	No information available	No information available	No information available	
Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers.					

Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization M	utagenicity	Sub-chronic Toxicity
N/DA N/DA		N/DA

### Section 12 - Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration Tox	xicit y to Sewage Bacteria
N/DA N/DA		N/DA	N/DA	N/DA

#### **Chemical Fate Information**

Chemical I are Information	
Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

# **Material Safety Data Sheet**

# **Crystal Nails GEL-LAC**

Page 4 of 6

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil

### Section 13 - Disposal Considerations

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

### Section 14 - Transport Information

DOT (49 CFR 172)	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (Ethyl Methacrylate), 3, PGII
Identification Number:	UN1993
Marine Pollutant:	No
Special Provisions:	T8, T31
Emergency Response Guidebook (ERG) #:	128
IATA (DGR):	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (Ethyl Methacrylate), 3, PGII
Class or Division:	3
UN or ID Number:	UN1993
Packaging Instructions:	
Emergency Response Guidance (ICAO)#:	
IMO (IMDG):	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (Ethyl Methacrylate), 3, PGII
Class or Division:	3.2
UN or ID Number:	UN1993
Special Provisions & Stowage/Segregation: None	
Emergency Schedule (EmS)#:	
Other Information:	Flash point = 23°C

## Section 15 - Regulatory Information

**US Federal Regulations** 

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U. S. Clean Air Act:  • NONE This product contains no ODS's
Clean Water Act: Priority Pollutant	This product contains the following chemicals listed under the U. S. Clean Water Act Priority Pollutant and Hazardous Substance List:  • Butyl Acetate, CAS# 123-86-4
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are:  • Immediate (acute) health hazard  • Delayed (chronic) health hazard  • Reactive hazard
RCRA	This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261):  • Ethyl Acetate CAS# 141-78-6, RCRA Code U112
SARA Title III: Section 302 (TPQ)	This product contains the following chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.  • Ethyl Acetate CAS# 141-78-6, RQ(lbs.): 5000  • Butyl Acetate, CAS# 123-86-4, RQ (Lbs): 5000

# **Material Safety Data Sheet**

# **Crystal Nails GEL-LAC**

Page 5 of 6

SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous chemical for emergency release notification ("CERCLA" List).					
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are:					
	Immediate (acute) health hazard					
	Delayed (chronic) health hazard					
	Reactive hazard					
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting					
	requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization					
	Act of 1986 and 40 CFR Part 372:					
	• Isopropyl Alcohol, CAS# 67-63-0					
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with					
	TSCA premanufacture notification requirements.					
TSCA Significant New Use Rule:	None of the chemicals listed have a SNUR under TSCA.					

**State Regulations** 

state Hegulations	
CA Right-to-Know Law: California No Significant Risk Rule:	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4 NONE
MA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4
NJ Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4
PA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4
FL Right-to-Know	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4
MN Right-to-Know	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4

**International Regulations** 

CDSL: Canadian Inventory	Hydroxypropyl methacrylate CAS #27813-02-1 is on the DSL List. WHMIS = D2B
(on Canadian Transitional List)	Hydroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS = n/da
	2-Hydroxyethyl methacrylate CAS# 868-77-9 is on the DSL List. WHMIS = n/da
	Isopropyl Alcohol CAS #67-63-0 is on the DSL list. WHMIS = B2, D2B
	Butyl Acetate CAS #123-86-4 is on the DSL list. WHMIS = B2, D1B, D2B
	Ethyl Acetate CAS# 141-78-6 is on the DSL List. WHMIS = n/da

### Labeling according to EC directives – 1999/45/EC

European Community:



#### Crystal Nails GEL-LAC

- HAZARD SYMBOLS: Xi: Irritant
- RISK PHRASES: R22: Harmful if swallowed, R36/38: Irritating to eyes and skin **R43:** May cause sensitization by skin contact.
- SAFETY PHRASES: **S18:** *Handle and open container with care*, **S24/25:** *avoid* contact with skin and eyes, \$36/37: Wear suitable protective clothing and gloves, **S38:** in case of insufficient ventilation, wear suitable respiratory equipment.

#### Section 16 - Other Information

#### EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

#### **Hazard Symbol:**

Xi - Irritants

F - Flammable

R10 – Flammable; R11 – Highly Flammable; R36 – Irritating to eyes; R43 - May cause sensitization by skin contact; R66 – Repeated exposure may cause skin dryness and cracking; R67 - Vapors may cause drowsiness and dizziness, R36/37/38 - Irritating to eyes, respiratory system and skin; R36/38 - Irritating to eyes and skin


S2 Keep out of the reach of children; S3/7 Keep container tightly closed in a cool place; S7 Keep container tightly closed; S16 Keep away from sources of ignition - No smoking; \$24/25 Avoid contact with skin and eyes; \$26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S27 Take off immediately all contaminated clothing; S28 After contact with skin, wash immediately with plenty of water; S29 Do not empty into drains; S30 Never add water to this product; S33 Take precautionary measures against static discharges; S35 This material and its container must be disposed of in a safe way; S36 Wear suitable protective clothing; S36/37 Wear suitable protective clothing and gloves; S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

#### **Hazard Rating System (Pictograms)**

# **Material Safety Data Sheet**

# **Crystal Nails GEL-LAC**

Page 6 of 6



MSDS Prepared by:	JRR
Revision History:	8/16/2010 Initial issue.

MAY CONTAIN THE FOLLOWING CHEMICALS:

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
·		OSHA ACGI H					
				TWA/STEL	TWA/STEL	IARC/NTP/OSH	
						A	
Titanium Dioxide	13463-67-7	236-675-5	Titanium Dioxide/CI77891	15 mg/m3	10 mg/m3	3/no/no	0-1
Yellow Iron Oxide	51274-00-1	257-098-5	Iron oxides/CI77492	N/E	N/E	Not Listed	0-1
Red Iron Oxide	1332-37-2	215-570-8	Iron Oxide/CI77491	N/E*	N/E*	Not Listed	0-1
D&C Red 7	5281-04-9	226-109-5	Red 7/CI15850	N/E	N/E	Not Listed	0-1
Synthetic Red Iron Oxide	1309-37-1	N/E	Iron Oxides/CI77491	N/E	N/E	Not Listed	0-1
(maroon)							
D&C Orange No.4	633-96-5	211-199-0	Orange 4/CI15510	N/E	N/E	Not Listed	0-1
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	Not Listed	0-1
Mica 12001-26-2		310-127-6	Mica	N/E	3 mg/m <sup>3</sup> Not	listed	0-1
FD&C Yellow #5	1934-21-0	217-699-5	Yellow 5/CI19140	N/DA	N/DA N/DA	Ι	0-1
D&C Red #6	5858-81-1	227-497-9	Red 6/CI15850 N/DA		N/DA	N/DA	0-1
D&C Red #34	6417-83-0	229-142-3	Red 34/CI15880 N/DA		N/DA	N/DA	0-1
Cosmetic Iron Blue	14038-43-8	237-875-5	Ferric Ferrocyanide/CI77510 N/	DA N/D	)A	N/DA	0-1
D&C Yellow #10	8004-92-0	N/DA	Yellow 10/CI47005/ E104	N/DA	N/DA	N/DA	0-1
Ultramarine Blue	57455-37-5	N/DA	Ultramarines/CI77007 N/DA		N/DA	N/DA	0-1
Manganese Violet	10101-66-3	233-257-4 M	anganese Violet/CI77742 N/I	DA .	N/DA	N/DA	0-1
FD&C Blue #1	3844-45-9	223-339-8	Blue 1/CI42090	N/E	N/E	Not Listed	0-1
D&C Black #2	1333-86-4	215-609-9	Carbon Black/CI77266	$3.5 \text{ mg/m}^3$	0.1 mg	Group 2B / A-4 /	0-1
·	·	·	·	0	PAH's/m <sup>3</sup>	Possible Select	

carbon black in presence of polycyclic aromatic

hydrocarbons (PAHs)

n Carcinogen

N/E - None Established N/DA-No Data Available
N/R - Not Reviewed N/A-Not Applicable

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.